


# ONE PLY FLAT POLYESTER WEB SLING BELT



## FEATURES

- Factor of Safety (Fos) – 6:1
- Working Temperature: 194°F (90°C) or below -40°F (-40°C).
- Lighter than the chain and steel wire rope sling
- Easy to use and high chemical resistance.
- Does not damage the material to be lifted. Positioning is fast and easy.
- Can tighten up the material to avoid slip while lifting the products.
- Only small storage space is required because of its flexibility.
- Medium initial investment cost. However, higher productivity, longer service life, easier handling and storage result in low total operating costs.
- Lightweight and excellent flexibility allow safer and easier handling of your valuable products.
- High resistance to chemical and oil contamination.
- Various sizes available for every application.
- Custom made slings for specific applications can be made to customer specifications.
- Special treatment gives excellent resistance to surface abrasion and cutting.
- Quality is maintained through constant research.

## ONE PLY FLAT POLYESTER WEB SLING BELT

WS01

Item Code(s)	COLOR	WIDTH		CAPACITY IN DIFFERENT SHAPE				THICKNESS
		Inch	mm	STRAIGHT (Ton)	BASKET (Ton)	CHOKER (Ton)	0-45 DEGREE (Ton)	
WS01-01	VOILET	1	25	0.5	1.0	0.4	0.7	3.75
WS01-02	GREEN	2	50	1.0	2.0	0.8	1.4	3.75
WS01-03	YELLOW	3	75	1.5	3.0	1.2	2.1	3.75
WS01-04	GREY	4	100	2.0	4.0	1.6	2.8	3.75
WS01-05	RED	5	125	2.5	5.0	2.0	3.5	3.75
WS01-06	BROWN	6	150	3.0	6.0	2.4	4.2	3.75
WS01-08	BLUE	8	200	4.0	8.0	3.2	5.6	3.75
WS01-10	ORANGE	10	250	5.0	10.0	4.0	7.0	3.75
WS01-12	ORANGE	12	300	6.0	12.0	4.8	8.4	3.75



## WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!  
Copyright©2023 | www.jblifting.com | All rights reserved