

CABLE LAID WIRE ROPE GROMMET ENDLESS SLING



DESCRIPTION & FEATURES

- **Standard:** EN13414-3
- **Construction:** Made from multiple wire ropes laid together to form a loop.
- **Purpose:** Used for lifting and rigging applications.
- **Versatility:** Can be used in various configurations for different lifting needs.
- **Durability:** Designed for heavy-duty use and long-term reliability.
- **Safety:** Ensures secure lifting and handling of loads.
- **Customization:** Can be customized to specific lengths and load capacities.
- **Applications:** Commonly used in industries like construction, maritime, and manufacturing.
- **Compliance:** Meets industry standards for safety and performance.
- CE, SWL & SSTC Mark shown on the product.



CABLE LAID WIRE ROPE GROMMET ENDLESS SLING

SWR-GRO

Angle Top Vertical Nominal Rope Decimeter	0 Degree Direct	0 Degree Choker Hitch
mm	t	t
24	9	7
27	11.5	9
30	14	11
33	17	13.5
36	20	16
39	23.5	19
42	27	21.5
48	35.5	28.5
54	45	36
60	55.5	44.5
66	69	55
72	84	68
78	102	81
84	121	97
90	144	115
98	168	135
102	198	157
108	227	182
114	262	210
156	700	-
152	750	-
168	800	-
174	850	-



WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!
Copyright©2023 | www.jblifting.com | All rights reserved

CABLE LAID WIRE ROPE GROMMET ENDLESS



CABLE LAID WIRE ROPE GROMMET ENDLESS

SWR-GRO

Angle Top Vertical	0 Degree	0 Degree
Nominal Rope Decimeter	Direct	Choker Hitch
mm	t	t
180	900	-
192	1000	-
216	1250	-
240	1500	-
258	1750	-
282	2000	-
300	2250	-
318	2500	-
354	3000	-
384	3500	-
414	4000	-
444	4500	-
474	5000	-
504	5500	-
528	6000	-
552	6500	-
576	7000	-
600	7500	-
624	8000	-
648	8500	-
682	9000	-
696	9500	-
Calculation Factors	1	0.8



The data of products dimension in the catalogue is just for reference!
 Copyright©2023 | www.jblifting.com | All rights reserved