

OUTRIGGER PADS

DESCRIPTION & FEATURES

- **Material:** UHMW Polyethylene
- **Density:** 0.981g/cm³
- **Molecular Weight:** ca 6.0
- **Tensile Strength:** 28 N/mm²
- **Breaking Strength:** 38 N/mm²
- **Modulus of Elasticity:** 1350 N/mm²
- **Torsional Stiffness +23C:** 350 N/mm²
- **Torsional Stiffness -40C:** 700 N/mm²
- **Shore hardness D:** 64



OUTRIGGER PADS

Size	Load Capacity	Weight	Load Spread Area
300×300×30mm	5 tonnes	2.7kg	0.09m ²
300×300×40mm	9 tonnes	3.6kg	0.19m ²
400×400×25mm	8 tonnes	4kg	0.16m ²
400×400×30mm	8 tonnes	4.8kg	0.16m ²
400×400×40mm	10 tonnes	6.4kg	0.16m ²
400×400×50mm	12 tonnes	8kg	0.16m ²
400×400×60mm	15 tonnes	9.6kg	0.16m ²
500×500×25mm	10 tonnes	6.3kg	0.25m ²
500×500×30mm	12 tonnes	7.5kg	0.25m ²
500×500×40mm	15 tonnes	10kg	0.25m ²
500×500×50mm	18 tonnes	12.5kg	0.25m ²
500×500×60mm	20 tonnes	15kg	0.25m ²
600×600×30mm	13 tonnes	10.8kg	0.36m ²
600×600×40mm	20 tonnes	14.4kg	0.36m ²
600×600×50mm	23 tonnes	18kg	0.36m ²
600×600×60mm	25 tonnes	21.6kg	0.36m ²
700×700×50mm	25 tonnes	24.5kg	0.49m ²
700×700×60mm	28 tonnes	29.4kg	0.49m ²
800×800×40mm	25 tonnes	25.6kg	0.64m ²
800×800×50mm	30 tonnes	32kg	0.64m ²
800×800×60mm	35 tonnes	38.4kg	0.64m ²
800×800×80mm	50 tonnes	51.2kg	0.64m ²
1000×1000×40mm	30 tonnes	40kg	1.00m ²
1000×1000×50mm	40 tonnes	48kg	1.00m ²
1000×1000×60mm	50 tonnes	60kg	1.00m ²
1000×1000×80mm	80 tonnes	80kg	1.00m ²
1000×1000×100mm	110 tonnes	100kg	1.00m ²
1200×1200×60mm	80 tonnes	86.4kg	1.44m ²
1200×1200×80mm	120 tonnes	115.2kg	1.44m ²
1200×1200×100mm	160 tonnes	144kg	1.44m ²
1500×1500×100mm	200 tonnes	225kg	2.25m ²
2000×1000×100mm	220 tonnes	200kg	2.00m ²
3000×1000×100mm	300 tonnes	300kg	3.00m ²



The data of products dimension in the catalogue is just for reference!
Copyright©2026 | www.jblifting.com | All rights reserved