


DESCRIPTION & FEATURES

- Standard: ASME B30.9.
- Material: Polyester.
- Factor of Safety 6:1 and 7:1.
- Proof load: 2 x WLL.
- Temperature: -40 °C to 90 °C.
- Lighter than the chain and steel wire rope sling.
- Does not damage the material to be lifted Positioning is fast and easy.
- Can tighten up the material to avoid slip while lifting the products.
- Only small storage space is required because of its flexibility.
- Medium initial investment cost. However, higher productivity, longer service life, easier handling and storage result in low total operating costs.
- Lightweight and excellent flexibility allow safer and easier handling of your valuable products.
- Various sizes available for every application.
- Custom made slings for specific applications can be made to customer specifications.
- Special treatment gives excellent resistance to surface abrasion and cutting.
- Quality is maintained through constant research.



Colour	Width			CAPACITY IN DIFFERENT SHAPES															
				Straight - 100%				Parallel Basket - 200%				Choker - 80%				Degree (0 - 45) Sling to Vertical			
																			
	inch	mm	mm	1 Ply	2 Ply	3 Ply	4 Ply	1 Ply	2 Ply	3 Ply	4 Ply	1 Ply	2 Ply	3 Ply	4 Ply	1 Ply	2 Ply	3 Ply	4 Ply
				Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne	Tonne
VIOLET	1	25	30	0.5	1.0	1.5	2.0	1.0	2.0	3.0	4.0	0.4	0.8	1.2	1.6	0.7	1.4	1.2	2.8
GREEN	2	50	60	1.0	2.0	3.0	4.0	2.0	4.0	6.0	8.0	0.8	1.6	2.4	3.2	1.4	2.8	2.4	5.6
YELLOW	3	75	90	1.5	3.0	4.5	6.0	3.0	6.0	9.0	12.0	1.2	2.4	3.6	4.8	2.1	4.2	3.6	8.4
GREY	4	100	120	2.0	4.0	6.0	8.0	4.0	8.0	12.0	16.0	1.6	3.2	4.8	6.4	2.8	5.6	4.8	11.2
RED	5	125	150	2.5	5.0	7.5	10.0	5.0	10.0	15.0	20.0	2.0	4.0	6.0	8.0	3.5	7.0	6.0	14.0
BROWN	6	150	180	3.0	6.0	9.0	12.0	6.0	12.0	18.0	24.0	2.4	4.8	7.2	9.6	4.2	8.4	7.2	16.8
BLUE	8	200	240	4.0	8.0	12.0	16.0	8.0	16.0	24.0	32.0	3.2	6.4	9.6	12.8	5.6	11.2	9.6	22.4
ORANGE	10	250	300	5.0	10.0	15.0	20.0	10.0	20.0	30.0	40.0	4.0	8.0	12.0	16.0	7.0	14.0	12.0	28.0
ORANGE	12	300	300	6.0	12.0	18.0	24.0	12.0	24.0	36.0	48.0	4.8	9.6	14.4	19.0	8.4	16.8	14.4	33.6



WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!
Copyright©2026 | www.jblifting.com | All rights reserved