

PORTABLE CRANE SCALE



DESCRIPTION & FEATURES

- **Standard:** ASME b30.26
- **Features:** Includes shackle, hook, high-precision sensors, A/D converters, and a 5-digit 1.2-inch ultra-bright digital display.
- **Stability:** Anti-shaking, anti-vibration, anti-swing filter ensures stable readings (<5 seconds stabilization).
- **Functions:** Instant peeling, delayed peeling, automatic accumulation.
- **Battery:** Long-lasting with up to 60 hours of continuous LED display, with over-discharge protection and power-saving features.



PORTABLE CRANE SCALE

DCS

Item Code (s)	Max Cap	Min Cap	Division	Dimension						N.W
				A	B	C	D	E	H	
	kg	kg	kg	mm	mm	mm	mm	mm	mm	kg
DCS-1	1000	10	0.5/0.2	95	345	27	230	160	470	11.1
DCS-2	2000	20	1/0.5	95	345	32	230	160	475	11.3
DCS-3	3000	30	1/0.5	95	345	37	230	160	570	12.2
DCS-5	5000	50	2/1	115	345	40	230	160	610	16.9
DCS-10	10000	100	5/2	115	345	50	230	160	725	30.3
DCS-15	15000	150	5/2	115	345	65	230	160	820	33
DCS-20	20000	200	10/5	225	345	85	230	160	1100	52
DCS-30	30000	300	10/5	260	345	105	230	160	1150	95



WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!
Copyright©2026 | www.jblifting.com | All rights reserved