

RETRACTABLE FALL ARRESTER



DESCRIPTION

Your Partner in Height Safety:

- Maximum Total Arrest Distance=1.8m
- Maximum Free Fall Distance=0.6m
- Maximum Capacity=100kg
- Maximum Fall Arrest Force=6kN
- The JB Lifting retractable fall arrester is a vital piece of equipment for anyone working at heights. It provides essential fall protection while maximizing worker mobility and comfort. Here's what makes the JB Lifting retractable fall arrester stand out

FEATURES

- **Standard:** ANSI Z-359.1 and EN 360:2002
- **SWR Strength:** 12kN
- **Retractable Design:** Automatically adjusts lifeline length, providing freedom of movement while minimizing slack.
- **Quick Activation:** Rapid response to sudden falls, arresting the descent almost immediately
- **Compact and Lightweight:** Easy to carry and minimally intrusive, facilitating comfort during use.
- **Durable Construction:** Engineered with polyamide cover for longevity and reliability.
- **Versatile Attachment Points:** Suitable for various anchorage options, enhancing flexibility in use.
- **Visual Indicator:** Clear signals or indicators to show if the device has been activated or needs inspection
- **Compliance:** Meets or exceeds industry safety standards, ensuring reliable fall protection.
- **Ease of Inspection:** Designed for straightforward visual checks and regular maintenance.
- **Integrated Energy Absorber:** Reduces impact forces on the user, enhancing safety during a fall.
- **User-Friendly:** Intuitive design for easy operation, even in stressful situations.



RETRACTABLE FALL ARRESTER

FAR

ItemCode(s)	MATERIAL	WIRE DIAMETER mm	LENGTH m
FAR-03M	Stainless Steel	4.0	3
FAR-06M	Stainless Steel	4.0	6
FAR-10M	Stainless Steel	4.0	10
FAR-15M	Stainless Steel	4.0	15
FAR-20M	Stainless Steel	4.0	20
FAR-25M	Stainless Steel	4.0	25
FAR-30M	Stainless Steel	4.0	30



WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!
Copyright©2026 | www.jblifting.com | All rights reserved