



DESCRIPTION & FEATURES

- **Safety Factor:** 5:1
- **Proof Load:** 2:1
- **Tensile Strength:** 1960 MPa
- **Meets and Exceeds:** SWL AS PER BS 1290, ASME B30.9 & EN 13414-1
- High Breaking Load.
- Excellent Life Time.
- Strong against Abrasion.
- Quality is maintained through constant research.
- CE, SWL & JB Lifting (JBL) Mark shown on the label.



STEEL WIRE ROPE SLING

Angle to the vertical	Single Leg Sling			Two Leg Sling		Three And Four Leg Sling	
	Vertical	Choker	Basket	0°-45°	45°-60°	0°-45°	45°-60°
							
Nominal Rope Dia (mm)	Working Load Limit (Tonnes)						
6	0.49	0.39	0.98	0.69	0.49	1.03	0.74
8 (5/16")	0.82	0.66	1.64	1.15	0.82	1.72	1.23
9	1.00	0.80	2.00	1.40	1.00	2.10	1.50
10 (3/8")	1.30	1.04	2.60	1.80	1.30	2.73	1.95
11	1.50	1.20	3.00	2.10	1.50	3.15	2.25
12	1.80	1.44	3.60	2.50	1.80	3.80	2.70
13 (1/2")	2.10	1.68	4.20	2.90	2.10	4.40	3.15
14 (9/16")	2.50	2.00	5.00	3.50	2.50	5.25	3.75
16 (5/8")	3.30	2.64	6.60	4.60	3.30	6.90	4.95
18	4.10	3.28	8.20	5.70	4.10	8.60	6.15
19 (3/4")	4.60	3.68	9.20	6.40	4.60	9.65	6.90
20	5.10	4.08	10.20	7.10	5.10	10.70	7.65
22 (7/8")	6.20	4.96	12.40	8.70	6.20	13.00	9.30
24	7.40	5.92	14.80	10.30	7.40	15.50	11.10
26 (1")	8.60	6.88	17.20	12.00	8.60	18.05	12.90
28 (1-1/8")	10.00	8.00	20.00	14.00	10.00	21.00	15.00
32 (1-1/4")	13.10	10.48	26.20	18.30	13.10	27.50	19.65
36 (1-3/8")	16.60	13.28	33.20	23.20	16.60	34.85	24.90
38 (1-1/2")	18.50	14.80	37.00	25.90	18.50	38.85	27.75
40	20.60	16.48	41.20	28.80	20.60	43.25	30.90
42 (1-5/8")	22.60	18.08	45.20	31.60	22.60	47.45	33.90
44 (1-3/4")	24.80	19.84	49.60	34.70	24.80	52.10	37.20
48 (1-7/8")	29.50	23.60	59.00	41.40	29.50	61.95	44.25
52 (2")	34.80	27.84	69.60	48.70	34.80	73.10	52.20
56 (2-1/4")	40.20	32.16	80.40	56.30	40.20	84.40	60.30
60	46.20	36.96	92.40	64.70	46.20	97.00	69.30
64 (2-1/2")	54.80	43.84	109.60	76.70	54.80	115.10	82.20
71 (2-3/4")	66.60	53.28	133.20	93.20	66.60	139.85	99.90
76 (3")	76.50	61.20	153.00	107.10	76.50	160.65	114.75
83 (3-1/4")	89.60	71.68	179.20	125.50	89.60	188.20	134.46
89 (3-1/2")	101.00	80.80	202.00	141.40	101.00	212.10	151.50
103 (4")	129.00	103.20	258.00	180.60	129.00	270.90	193.50



The data of products dimension in the catalogue is just for reference!
Copyright©2026 | www.jblifting.com | All rights reserved