


DESCRIPTION & FEATURES

- **Cable Pressure** : 200psi Rating.
- **Tensile Strength**: 1770 MPA
- **Purpose**: Prevent hose and accidental separation.
- **Material**: Made from steel cables with spring loaded loops.
- **Function**: Securely attach hoses and fittings to control movement.
- **Safety Benefit**: Reduces injury and damage risks in high pressure systems.
- **Versatile**: Suitable for compressed air and hydraulic applications.
- **Durable**: Withstands high pressures and frequent use.
- **Easy Installation**: Simple to install for added security.
- **Compliance**: Meets safety regulations for industrial use.
- **Maintenance**: Requires periodic inspection for continued safety.
- **Essential**: Enhances workplace safety in industrial settings.
- Electro Galvanized
- CE, SWL & JB Lifting (JBL) Mark shown on the product.



WHIPCHECK SAFETY CABLES

WHC

Item Code	Cable Diameter D1		Hose Diameters D2		Min. Breaking Strain of Cable kg	Length L Meter	Weight per cable kg
	Inch	mm	Inch	mm			
WHC03x0.5	1/8	3	1/2 to 1.25	12 to 32	588	0.6	0.09
WHC06x01	1/4	6	1.5 to 3	38 to 76	2350	1	0.52
WHC08x01	5/16	8	3.5 to 6	88 to 152	3750	1	0.8



WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!
Copyright©2026 | www.jblifting.com | All rights reserved