

DESCRIPTION & FEATURES

- **Standard:** Calibrated to DIN 766.
- **Material:** High-quality Grade 3 carbon steel.
- **Finish:** Hot-dip galvanized for superior rust and corrosion resistance.
- **Features:** Short link design, tested and calibrated for smooth operation in windlasses.
- **Applications:** Ideal for maritime anchoring, mooring, fences, and general industrial use.
- **Safety:** Not suitable for overhead lifting or hoisting applications.



GALVANIZED CHAIN

Chain Size		Pitch			Width		Length per 11 Links			Working Load	Test Force	Min. Breaking Force
D	tolerance	L	tolerance		Min. b	Max. B	11 L	tolerance				
mm		mm			mm	mm	mm			kg	kN	kN
4	±0.2	16	0.3	-0.2	4.8	13.6	176	0.8	-0.4	200	5	8
5	±0.2	18.5	0.4	-0.2	6	17	204	0.9	-0.5	320	8	12.5
6	±0.2	18.5	0.4	-0.2	7.2	20.4	204	0.9	-0.5	400	10	16
7	±0.3	22	0.4	-0.2	8.4	23.8	242	1.1	-0.5	630	16	25
8	±0.3	24	0.4	-0.2	9.6	27.2	264	1.2	-0.6	800	20	32
9	±0.4	27	0.5	-0.3	10.8	30.6	297	1.3	-0.7	1,000	25	40
10	±0.4	28	0.5	-0.3	12	36	308	1.4	-0.7	1,250	32	50
11	±0.4	31	0.5	-0.3	13.2	40	341	1.5	-0.8	1,600	40	63
13	±0.5	36	0.6	-0.3	15.6	47	396	1.7	-0.9	2,000	50	80
14	±0.6	41	0.7	-0.4	16.8	50	451	2	-1	2,500	63	100
16	±0.6	45	0.8	-0.4	19.2	58	495	2.2	-1.1	3,200	80	125
18	±0.9	50	0.8	-0.4	21.6	65	550	2.5	-1.2	4,000	100	160
20	±1.0	56	1	-0.5	24	72	616	2.8	-1.4	5,000	125	200
23	±1.2	64	1.1	-0.5	27.6	83	704	3.2	-1.6	6,300	160	250
26	±1.3	73	1.2	-0.6	31.2	94	803	3.6	-1.8	8,000	200	320
28	±1.4	78	1.3	-0.6	33.6	101	858	3.8	-2	10,000	250	400
30	±1.5	84	1.4	-0.7	36	108	924	4.2	-2.1	11,200	280	450
32	±1.6	90	1.5	-0.7	38.4	115	990	4.5	-2.2	12,500	320	500
36	±1.8	101	1.7	-0.8	43.2	130	1,111	5	-2.5	16,000	400	630
40	±2.0	112	1.9	-0.8	48	144	1,232	5.6	-2.8	20,000	500	800
42	±2.1	118	2	-1	50	151	1,298	5.8	-3	22,400	560	900



WARNING

Never exceed Working Load Limit

The data of products dimension in the catalogue is just for reference!
Copyright©2026 | www.jblifting.com | All rights reserved